UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/678,222	10/06/2003	Mark Walter Chamberlain	HAR65 045	1579

7590   02/21/2008

MARK C. COMTOIS
Duane Morris LLP
Suite 700
1667 K Street, N.W
Washington, DC 20006

EXAMINER
HERNANDEZ, JOSIAH J

ART UNIT	PAPER NUMBER
2626	

MAIL DATE	DELIVERY MODE
02/21/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

PTOL-90A (Rev. 04/07)

	Application No.	Applicant(s)
Office Action Summary	10/678,222	CHAMBERLAIN, MARK WALTER
	Examiner	Art Unit	
	Josiah Hernandez	2626	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on <u>06 October 2003</u>.

2a)☒ This action is **FINAL**.   2b)☐ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) *1-6,8-29 and 31-44* is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) *1-6,8-29 and 31-44* is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☒ The drawing(s) filed on <u>06 October 2003</u> is/are: a)☒ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All   b)☐ Some * c)☐ None of:

        1.☐ Certified copies of the priority documents have been received.

        2.☐ Certified copies of the priority documents have been received in Application No. _____.

        3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)
2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
3) ☐ Information Disclosure Statement(s) (PTO/SB/08)
    Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____.
5) ☐ Notice of Informal Patent Application
6) ☐ Other: _____.

DETAILED ACTION

Response to Arguments

1.   Applicant's arguments filed 11/26/2007 have been fully considered but they are not persuasive.

The applicant argues that the references used do not teach an estimated noise history to signal frames to computer a spectral gain function, computing SNR magnitudes of the signal frames, and detecting voice activity as a function of conditional comparisons of received signal-to-noise ratios and average signal-to-noise ration thresholds.

Johnson (US 6,415,253) teaches a system that computes the average energy of the overall signals then compares it to the incoming signals and analyzes the relationship between the energies of which are composed of calculated SNR values and used to determine levels of SNR in the received signal and the average signals (column 8 lines 46-67).

Claim Rejections - 35 USC § 103

1.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or

described as set forth in section 102 of this title, if the differences between the

subject matter sought to be patented and the prior art are such that the subject

matter as a whole would have been obvious at the time the invention was made to a

person having ordinary skill in the art to which said subject matter pertains.

Patentability shall not be negatived by the manner in which the invention was made.

2.   Claims 1-10, 19, 22, 24-26, 42-44 are rejected under 35 U.S.C. 103(a) as being

unpatentable over Johnson (US 6,415,253) in view of Adlersberg et al. (US 5,012,519).

As to claim 1, Johnson discloses a method of reducing a noise component of an input

speech signal (noise suppression device Abstract lines 1-3) comprised of signal frames

on a channel (dividing the received signal into data frames Abstract lines 3-5)

comprising the steps of: applying a windowed Fourier transformation to said signal

frames (applying fast Fourier transform to the appended data frames, abstract lines 7-

9); approximating signal magnitudes of said signal frames (producing sets of magnitude

components of the frequency spectrum for each of the frames, column 7 lines 20-24);

computing Signal-to-Noise Ratio magnitudes of said signal frames (in spectral

subtraction a signal-to-noise ratio is calculated by considering the magnitudes of the

speech and noise signal, column 1 lines 55-60); detecting voice activity in said channel

(voice activity, which is the speech signal, is detected from the input channel for the use

of signal-to-noise ratio, column 1 lines 56 and 57; column 2 line 61) as a function of

conditional comparisons of received signal-to-noise ratios and average signal-to-noise

ratio thresholds (computing the average energy of the overall signals then compares it

to the incoming signals and analyzes the relationship between the energies of which are

composed of calculated SNR values and used to determine levels of SNR in the

received signal and the average signals, column 8 lines 46-67); detecting noise activity

in said channel (noise activity, which is the noise signal, is detected from the input

channel for the use of signal-to-noise ratio, column 1 lines 57 and 58; column 2 line 61);

estimating gain in said signal frames, producing gain multiplicative factors based on the

noise spectral estimate and frequency spectrum components (the frequency

components are received from the windowed frame of signals, see column 3 lines 50 -

57); applying said spectral gain function to the components of said windowed Fourier

transformation (applying the gain factor to the frequency components, column 3 lines

57-60); and, applying an inverse Fourier transform to said signal frames thereby

reconstructing a noise reduced output signal frame (once the noise has been reduced

from the signal an inverse Fast Fourier Transform, column 1 lines 62-64, is used to

convert the frequency components of the frames into time domain and reconstructing the noise reduced signal, column 3 lines 59-61.

Johnson does not specifically disclose applying an estimated noise history to signal frame. Adlersberg teaches a noise reduction system (see title), of which applies an estimated noise history to signal frames to compute a spectral gain function, the gain function that is calculated depends on the adaptive noise estimates, which include averages of historical values, column 2 lines 50-52 and 56; It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the noise reduction method of Johnson with historic SNR values for gain function calculation as disclosed by Adlersberg. Doing so would have given a more accurate noise estimator for the gains in each frame that change according to the SNR values.

As to claim 2, Johnson does not specifically disclose using a database for stored historical SNR values. Adlersberg teaches using current and previous noise estimates (see column 2 lines 58 &59), their storage imply using a database. It would have been obvious to one having ordinary skill in the art at the time the invention was made that if more accurate calculations are made for SNR from historical values, these historical values would have to be stored in a list or in some organized fashion that constitute a database.

As to claim 3, Johnson discloses estimating noise values from signal frames, in the abstract it clearly states that an input signal is converted into frames and the signal is processed as frames from the beginning of the process until the end, (a SNR value is generated for the speech in each frequency component (the frequency components are received from the windowed frame of signals (see column 3 lines 50 and 51))) (see column 1 lines 57 and 58). Johnson does not specifically disclose applying an estimated noise history to signal frame. Adlersberg teaches a noise reduction system (see abstract), of which applies an estimated noise history to signal frames to compute a spectral gain function (the gain function that is calculated depends on the prior and posterior signal-to-noise ratios, which are historical values) (see column 7 lines 45-50); It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the noise reduction method of Johnson with historic SNR values for gain function calculation as disclosed by Adlersberg. Doing so would have given an accurate statistical estimator of how the gains in each frame should change according to the past SNR values.

As to claim 4, Johnson discloses using signal frames that are overlapped and added to previous signal frames (Johnson teaches overlapping adjacent frames (see column 15 lines 33-36) and using the immediately previous frame (see column 15 lines 41-46).

As to claim 5, Johnson discloses filtering said signal-to-noise ratio

magnitude and signal magnitude prior to detecting voice activity in channel

(Johnson teaches using a filter to process a SNR magnitude values, which come

from the signal and noise magnitude values. These values are then used to

calculate a gain value in order to apply to the frequency spectrum once the voice

activity has been detected (at this point the gain ratio would be applied to the

voice activity, once the SNR values are detected the gain values are calculated

in order to use on the components when undesirable speech is detected, which

is done by the VAD column 4 lines 1-7, therefore the SNR values are filtered

before detecting voice activity, see column 1 lines 52-60).

As to claim 6, Johnson discloses applying a windowed Fourier transform

(a transform obtains frequency spectrum components from the windowed frame

of signals, column 3 lines 49-52) on noise reduced output signal frame (once the

noise has been reduced from the signal an inverse transformer (of which is an

inverse Fast Fourier Transform (see column 1 lines 62-64)) is used to convert the

frequency components of the frames into time domain and reconstructing the

noise reduced signal) (see column 3 lines 59-61).

As to claim 8, 25, and 43, Johnson does not specifically disclose said

noise component is Gaussian. Adlersberg teaches reducing noise signal from a

speech signal; the noise signal being a Gaussian signal, column 7 lines 25-28. It

would have been obvious to one having ordinary skill in the art at the time the

invention was made to have modified the noise signal disclosed in Johnson with

the Gaussian signal in Adlersberg. Gaussian noise signals are a very common

noise signal and in order to effectively reduce all noise signals, Gaussian noise

signals would also have to be included.

As to claim 9, 24, and 42, Johnson discloses ramped noise (a non-

stationary noise like a car passing at a distance; Johnson teaches non-stationary

noise that can come from a passing car, column 3 lines 16-19).

As to claim 10, 26, and 44, Johnson discloses non-stationary noise (see

column 3 lines 16 & 17).

As to claim 19, Johnson discloses noise reduced output signal frame is

overlapped and added to previous noise reduced output signals frame (Johnson

teaches overlapping adjacent frames, column 15 lines 33-36) and using the

immediately previous frame (see column 15 lines 41-46).

As to claim 22, Johnson discloses the method of reducing noise wherein

the entire process is repeated responsive to the presence of additional input

speech signal frames (Johnson a state transition diagram of the enclosed

invention where the process is repeated upon receiving speech signals) (see figure 2).

As to claim 43, Johnson discloses the use of ramped noise (ramped noise is defined as a non-stationary noise like a car passing at a distance. Johnson teaches using non-stationary noise that can come from a passing car) (see column 3 lines 14-19).

As to claim 44, Johnson discloses the use of non-stationary noise (see column 3 lines 14-19).

3.   Claims 20, 21, 23, 34-42 are rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson (US 6,415,253) in view of Adlersberg et al. (US 5,012,519) as applied to claims 1, 23, 28 and 35 and in further view Sluijter et al. (US 6,985,855).

As to claim 20, Johnson discloses using the average noise from the input signal (see column 8 lines 46-55). Johnson does not disclose specifically average noise is filtered from the noise reduced output signal frame. Sluijter teaches a post-process of filtering an output signal that passes through a synthesis filter and using a threshold value to see if noise exists in the signal (see column 2 lines 47-59). When noise is detected it is then reduced, column 11

lines 50-60. It would have been obvious to one having ordinary skill in the art at

the time the invention was made to have modified the noise signal disclosed in

Johnson with the post-process of Sluijter. Making the post-processing means

dependent of the background noise the speech quality can be improved (see

column 2 lines 55-60).

As to claim 21, Johnson does not disclose specifically the step of filtering

said average noise comprises adapting a post-processed noise level to an

acceptable level. Sluijter teaches a post-process of filtering an output signal that

passes through a synthesis filter and using a threshold value to see if noise

exists in the signal (see column 2 lines 47-59). When noise is detected it is then

reduced, column 11 lines 50-60. It would have been obvious to one having

ordinary skill in the art at the time the invention was made to have modified the

noise signal disclosed in Johnson with the post-process of Sluijter. Making the

post-processing means dependent of the background noise the speech quality

can be improved (see column 2 lines 55-60).

As to claim 23, Johnson discloses a method of filtering a noise component

from an input speech signal comprised of signal frames the improvement (see

abstract lines 1-10) comprising the steps of: estimating said noise component

present in the speech signal (noise activity (which is the noise signal) is detected

from the input channel for the use of signal-to-noise ratio) (see column 1 lines 57

and 58); modifying said input speech signal based on an estimation of the noise component (Johnson teaches applying the gain factor to in order to modify the frequency components (the frequency components are received from the windowed frame of signals (see column 3 lines 50 and 51)) in order to attenuate the spectrum) (see column 3 lines 55-60); identifying speech segment from said noise component (voice activity (which is the speech signal) is detected from the input channel for the use of signal-to-noise ratio) (see column 1 lines 56 and 57) as a function of conditional comparisons of received signal-to-noise ratios and average signal-to-noise ratio thresholds (computing the average energy of the overall signals then compares it to the incoming signals and analyzes the relationship between the energies of which are composed of calculated SNR values and used to determine levels of SNR in the received signal and the average signals, column 8 lines 46-67); Johnson does not specifically disclose adapting a post-processed noise component to an acceptable, noise-reduced level. Sluijter teaches a post-process of filtering an output signal that passes through a synthesis filter and using a threshold value to see if noise exists in the signal (see column 2 lines 47-59). When noise is detected it is then reduced, column 11 lines 50-60. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the noise signal disclosed in Johnson with the post-process of Sluijter. Making the post-processing means dependent of the background noise the speech quality can be improved (see column 2 lines 55-60).

As to claim 34, Johnson does not disclose specifically said second filtering

means adapts a post-processed noise level to an acceptable level. Sluijter

teaches a post-process of filtering an output signal that passes through a

synthesis filter and using a threshold value to see if noise exists in the signal (see

column 2 lines 47-59). When noise is detected it is then reduced, column 11

lines 50-60. It would have been obvious to one having ordinary skill in the art at

the time the invention was made to have modified the noise signal disclosed in

Johnson with the post-process of Sluijter. Making the post-processing means

dependent of the background noise the speech quality can be improved (see

column 2 lines 55-60).

As to claim 35, Johnson discloses a method of noise cancellation in a

received speech signal comprised of signal frames (Johnson teaches a noise

suppression (of which cancels noise) device) (see abstract lines 1-3) comprising

the steps of: applying a windowed Fourier transform to said signal frames

(Johnson discloses applying fast Fourier transform to the appended data frames)

(see abstract lines 7-9); estimating a noise component present in said signal

frames (noise activity (which is the noise signal) is detected from the input

channel/components for the use of signal-to-noise ratio) (see column 1 lines 57

and 58); modifying said signal frames based on a calculated noise estimate (this

is done by producing gain multiplicative factors based on the noise spectral

estimate and frequency spectrum components (the frequency components are received from the windowed frame of signals (see column 3 lines 50 and 51))) (see column 3 lines 55-57); identifying speech segments from said noise component (voice activity (which is the speech signal) is detected from the input channel for the use of signal-to-noise ratio) (see column 1 lines 56 and 57) as a function of conditional comparisons of received signal-to-noise ratios and average signal-to-noise ratio thresholds (computing the average energy of the overall signals then compares it to the incoming signals and analyzes the relationship between the energies of which are composed of calculated SNR values and used to determine levels of SNR in the received signal and the average signals, column 8 lines 46-67).

Johnson does not disclose specifically adapting a post-processed noise level to an acceptable level Sluijter teaches a post-process of filtering an output signal that passes through a synthesis filter and using a threshold value to see if noise exists in the signal (see column 2 lines 47-59). When noise is detected it is then reduced, column 11 lines 50-60. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the noise signal disclosed in Johnson with the post-process of Sluijter. Making the post-processing means dependent of the background noise the speech quality can be improved (see column 2 lines 55-60).

As to claim 36, Johnson discloses approximating magnitudes of said signal frames (Johnson discloses producing sets of magnitude components of the frequency spectrum for each of the frames) (see column 7 lines 20-24); computing Signal-to-Noise Ratio magnitudes of said signal frames (Johnson explains that in spectral subtraction a signal-to-noise ratio is calculated by considering the magnitudes of the speech and noise signal) (see column 1 lines 55-60); detecting any noise component on said channel (noise activity (which is the noise signal) is detected from the input channel for the use of signal-to-noise ratio) (see column 1 lines 57 and 58); detecting stepping noise component on said channel (noise activity (which is the noise signal) is detected from the input channel for the use of signal-to-noise ratio (see column 1 lines 57 and 58) and the noise component is a stepping noise like a non-stationary noise (ramped noise is defined as a non-stationary noise like a car passing at a distance. Johnson teaches using non-stationary noise that can come from a passing car) (see column 3 lines 14-19)); and estimating a gain in said noise component (this is done by producing gain multiplicative factors based on the noise spectral estimate and frequency spectrum components (the frequency components are received from the windowed frame of signals (see column 3 lines 50 and 51))) (see column 3 lines 55-57).

As to claim 37, Johnson discloses noise components comprising ramping noise components, non-stationary noise components, or both (ramped noise is

defined as a non-stationary noise like a car passing at a distance. Johnson

teaches using non-stationary noise that can come from a passing car) (see

column 3 lines 14-19).

As to claim 38, Johnson does not specifically disclose computing a spectral

gain function from an estimated noise history. Adlersberg teaches a noise reduction

system (see abstract), of which applies an estimated noise history to signal frames

to compute a spectral gain function (the gain function that is calculated depends on

the prior and posterior signal-to-noise ratios, which are historical values) (see

column 7 lines 45-50); It would have been obvious to one having ordinary skill in the

art at the time the invention was made to have modified the noise reduction method

of Johnson with historic SNR values for gain function calculation as disclosed by

Adlersberg. Doing so would have given an accurate statistical estimator of how the

gains in each frame should change according to the past SNR values.

As to claim 39, Johnson discloses applying an inverse Fourier transform

thereby reconstructing noise reduced signal frames (of which is an inverse Fast

Fourier Transform (see column 1 lines 62-64)) is used to convert the frequency

components of the frames into time domain and reconstructing the noise reduced

signal) (see column 3 lines 59-61). Johnson also discloses applying said

spectral gain function to the components of a Fourier transform of said signal

frames (Johnson teaches applying the gain factor to the frequency components

(the frequency components are received from the windowed frame of signals (see column 3 lines 50 and 51)) in order to attenuate the spectrum) (see column 3 lines 55-60). Johnson teaches applying said spectral gain function to the real and imaginary components of a Fourier transform of said signal frames. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the noise reduction method of Johnson with the description of real and imaginary components in its Fourier transform calculation, since Johnson discloses using the frequency components with the Fourier transform and a Wiener filter, the Fourier transform that is used with the Wiener filter includes real and imaginary parts in its calculation in order to describe the speech signal.

As to claim 40, Johnson discloses identifying speech segments from said noise component further comprises applying a windowed Fourier transform on an output signal frame (once the noise has been reduced from the signal an inverse transformer (of which is an inverse Fast Fourier Transform (see column 1 lines 62-64)) is used to convert the frequency components of the frames into time domain and reconstructing the noise reduced signal) (see column 3 lines 59-61).

As to claim 41, Johnson does not specifically disclose adapting a post-precessed noise component to an acceptable level further comprises filtering average noise from an output signal frame. Sluijter teaches a post-process of

filtering an output signal that passes through a synthesis filter and using a threshold value to see if noise exists in the signal (see column 2 lines 47-59). When noise is detected it is then reduced, column 11 lines 50-60. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the noise signal disclosed in Johnson with the post-process of Sluijter. Making the post-processing means dependent of the background noise the speech quality can be improved (see column 2 lines 55-60).

As to claim 42, Johnson discloses the use of Gaussian noise component (Johnson refers to a related art that uses similar method to reduce noise and the noise component is an additive white noise). It would have been obvious to one having ordinary skill in the art at the time the invention was made that a Gaussian noise component that has a probability density function, which is commonly used as additive white noise to yield additive white Gaussian noise.

4.   Claim 27 is rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson (US 6,415,253) in view of Adlersberg et al. (US 5,012,519) as applied to claim 23 and in further view of Hermansky et al. (US 6,098,038).

As to claim 27, Johnson discloses applying said spectral gain function to the real and imaginary components of a fourier transform of said input speech signal (Johnson teaches applying the gain factor to the frequency components (the frequency components are received from the windowed frame of signals (see column 3 lines 50 and 51)) in order to attenuate the spectrum) (see column 3 lines 55-60); and, processing said Fourier transform by an inverse Fourier transform thereby reconstructing a noise reduced speech signal (once the noise has been reduced from the signal an inverse transformer (of which is an inverse Fast Fourier Transform (see column 1 lines 62-64)) is used to convert the frequency components of the frames into time domain and reconstructing the noise reduced signal) (see column 3 lines 59-61).

Johnson or Adlersberg does not specifically disclose using a histogram. Hermansky teaches using an estimated noise histogram and/or a generated noise histogram compute a spectral gain function (this is done by computing the histogram of the noise signal's amplitudes. The peak of the smoothed histogram is chosen as the noise amplitude estimate. These calculations are further used to estimate the noise-to-signal ratio, column 4 lines 35-43). It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the spectral gain function method of Johnson with the use of histogram calculations as disclosed by Hermansky. Doing so would allow to make a more accurate estimation of a stationary noise signal level and clean

speech signal. Since the power of the clean speech signal is unknown, the power

of the available noisy signal can be used, thus obtaining an estimate of the noisy

signal-to-noise ratio, column 4 lines 39-41).

5.   Claims 11-15, 18, and 28-32 are rejected under 35 U.S.C. 103(a) as being

unpatentable over Johnson (US 6,415,253) in view of Adlersberg et al. (US 5,012,519)

as applied to claims 1 and 28, and in further view of Bizjak et al. (US PGPub

2003/0035549) and Hermansky et al. (US 6,098,038).

As to claim 11, Johnson and Adlersberg do not specifically disclose

sampling a slew rate of said noise reduced output signal frame. Bizjak teaches a

signal processing method where the slew rate is calculated and applied to non-

linear smoothing which keeps the output signal under the clipping threshold (see

paragraph [0326] lines 12-17). It would have been obvious to one having ordinary

skill in the art at the time the invention was made to have modified the spectral

gain function method of Johnson with the use of the calculation of the slew rate

as disclosed by Bizjak, by doing so it would have been easier to detect ramping

noise signals since the slew rate calculate the rate of change of the noise signal

in time (see paragraph [0326] lines 14-18).

As to claim 12, Johnson discloses deciding to continue said sampling, the

sampling can be done a 8kHz and will continue until a desired amount of bits

have been sampled. The system decides to continue sampling until the desired

sampling bits are accomplished, column 6 lines 13-20. Johnson does not

specifically disclose using a counter, slew rate, or histogram. Bizjak teaches

using a clip event counter as an input and updating the counter by using a reset

clip counter, in order to reset a counter the counter would have to be started

initially (see table A in paragraph [0237]). Bizjak also teaches adjusting the

sample slew rate; the slew rate is calculated and applied to non-linear smoothing

which keeps the output signal under the clipping threshold (see paragraph [0326]

lines 12-17). Hermansky teaches encoding and a noise sample and decoding a

noise estimate, in order for the noise signal to be used for further calculations it

would have to be encoded from an input signal, column 4 lines 35-37 and

decoded in its raw form for further analysis. Hermansky also teaches using an

estimated noise histogram and/or a generated noise histogram compute a

spectral gain function (this is done by computing the histogram of the noise

signal's amplitudes. The peak of the smoothed histogram is chosen as the noise

amplitude estimate. These calculations are further used to estimate the noise-to-

signal ratio, column 4 lines 35-43), every time that a histogram calculation would

be used it would have to be updated so it can represent the new data and

normalized to the new setting so the calculations can be accurate. A weighted

histogram bin is represented by a number of amplitudes that have been

represented by histogram calculations and have certain weights or importance

and the peak amplitude is chosen as the noise amplitude. It would have been

obvious to one having ordinary skill in the art at the time the invention was made

to have modified the noise reduction method as disclosed by Johnson with the

counter and slew rate of Bizjak and the histogram of Hermansky. Doing so would

allow to keep track of the slew rate with the counter allowing to detect non-

stationary noise and using a histogram would allow to make a more accurate

estimation of a stationary noise signal level and clean speech signal. Since the

power of the clean speech signal is unknown, the power of the available noisy

signal can be used, thus obtaining an estimate of the noisy signal-to-noise ratio,

Hermansky column 4 lines 39-41).

As to claim 13, Johnson and Adlersberg do not specifically disclose

measuring an error period. Bizjak teaches sampling a slew rate to make a

distinction of speed of smoothing (see paragraph [0327] lines 1-10) and

calculating the error of speed tracking (see paragraph [0338] lines 20-24). It

would have been obvious to one having ordinary skill in the art at the time the

invention was made to have modified the spectral gain function method of

Johnson with the use of the calculation of the error as disclosed by Bizjak, by

doing so it would have been easier to calculate ramping noise signals with the

use of errors and threshold values (see paragraph [0338] lines 20-24).

As to claim 14, Johnson and Adlersberg do not specifically disclose a

counter reset. Bizjak teaches using a clip event counter as an input and a reset

clip counter as outputs (see table A in paragraph [0237]). It would have been

obvious to one having ordinary skill in the art at the time the invention was made

to have modified the spectral gain function method of Johnson with the use of a

counter reset as disclosed by Bizjak. Doing so would allow to calculate new

values that do not carry old values that might compromise the integrity of the

present values.

As to claim 15, Johnson discloses noise reduced output signal frame is

overlapped and added to previous noise reduced output signals frame (Johnson

teaches overlapping adjacent frames (see column 15 lines 33-36) and using the

immediately previous frame (see column 15 lines 41-46).

As to claim 18, Johnson discloses the method of reducing noise wherein

the entire process is repeated responsive to the presence of additional input

speech signal frames (Johnson a state transition diagram of the enclosed

invention where the process is repeated upon receiving speech signals) (see

figure 2).

As to claim 28, Johnson discloses a system for noise cancellation (see abstract lines 1-3) comprising: a first input means operable connected to a processor said first input means receiving a speech signal (Johnson explains that in spectral subtraction an input signal is received and converted to components (see column 1 lines 47-50) by a digital signal processor (see column 5 lines 60-67)); an output means operable connected to said first and second input means and said output speech signal (The noise suppression device modifies magnitude of the time domain data based on the voicing information outputted form the voice activity detector (see abstract 16-19)); and, a processing means operably connected to said first and second input means and said output means (this is done by the digital signal processor (see column 5 lines 60-67)), said processing means comprising a control and storage means (see column 6 lines 1-6), a first filtering means, a second filtering means (a first or pre-filter is used to remove dc components and a second (Wiener) filter is used to smoothen the signals (see abstract)), a voice activity detector (see abstract lines 18 and 19), and a sampling and adjustment means (the sampling is done by the breaking of the signals into components (see abstract lines 1-5) and the adjusting is done by the automatic gain control module (see figure1 # 30)), said voice activity detector detects and attacks noise activity on a frequency channel as a function of conditional comparisons of received signal-to-noise ratios and average signal-to-noise ratio thresholds (computing the average energy of the overall signals then compares it to the incoming signals and analyzes the relationship between the

energies of which are composed of calculated SNR values and used to determine levels of SNR in the received signal and the average signals, column 8 lines 46-67).

Johnson does not specifically disclose using a second input means operably connected to said processor wherein historical speech and noise data may be entered into a control and storage means for access by said processor. Adlersberg teaches a noise reduction system (see abstract), of which applies an estimated noise history to signal frames to compute a spectral gain function (the gain function that is calculated depends on the prior and posterior signal-to-noise ratios, which are historical values) (see column 7 lines 45-50); Johnson also does not disclose specifically using a noise step detector. Bizjak teaches a signal processing method where the slew rate is calculated and applied to non-linear smoothing which keeps the output signal under the clipping threshold (see paragraph [0326] lines 12-17). It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the noise reduction method of Johnson with historic SNR values for gain function calculation as disclosed by Adlersberg and with the use of the calculation of the slew rate as disclosed by Bizjak. Doing so would have given an accurate statistical estimator of how the gains in each frame should change according to the past SNR values and it would have also been easier to calculate ramping noise signals since the slew rate calculate the rate of change of the noise signal in time (see Bizjak paragraph [0326] lines 14-18).

As to claim 29, Johnson discloses first filtering means filters Signal-to-Noise Ratio magnitudes and signal magnitudes (Johnson clearly explains that in the first process of spectral subtraction for noise suppression a filter is used to estimate the power spectral density, thereby generating a signal-to-noise ratio (see column 1 lines 52-55).

As to claim 31, Johnson discloses the noise activity being ramping, non-stationary, or both (ramped noise is defined as a non-stationary noise like a car passing at a distance. Johnson teaches using non-stationary noise that can come from a passing car) (see column 3 lines 14-19).

As to claim 32, Johnson does not disclose specifically the noise step detector detects and attacks a stepping noise component on said frequency channel. Bizjak teaches a signal processing method where the slew rate is calculated and applied to non-linear smoothing which keeps the output signal under the clipping threshold (see paragraph [0326] lines 12-17). It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the spectral gain function method of Johnson with the use of the calculation of the slew rate as disclosed by Bizjak, by doing so it would have been easier to calculate ramping noise signals since the slew rate calculate the rate of change of the noise signal in time (see paragraph [0326] lines 14-18).

6.   Claims 16 and 17 are rejected under 35 U.S.C. 103(a) as being unpatentable

over Johnson (US 6,415,253) in view of Adlersberg et al. (US 5,012,519) as applied to

claims 1, 23, 28 and 35 and in further view Sluijter et al. (US 6,985,855) and in further

view of Bizjak et al. (US PGPub 2003/0035549) and Hermansky et al. (US 6,098,038).

        As to claim 16, Johnson discloses using the average noise from the input

signal (see column 8 lines 46-55). Johnson does not disclose specifically

average noise is filtered from the noise reduced output signal frame. Sluijter

teaches a post-process of filtering an output signal that passes through a

synthesis filter and using a threshold value to see if noise exists in the signal (see

column 2 lines 47-59). When noise is detected it is then reduced, column 11

lines 50-60. It would have been obvious to one having ordinary skill in the art at

the time the invention was made to have modified the noise signal disclosed in

Johnson with the post-process of Sluijter. Making the post-processing means

dependent of the background noise the speech quality can be improved (see

column 2 lines 55-60).

        As to claim 17, Johnson does not disclose specifically the step of filtering

said average noise comprises adapting a post-processed noise level to an

acceptable level. Sluijter teaches a post-process of filtering an output signal that

passes through a synthesis filter and using a threshold value to see if noise

exists in the signal (see column 2 lines 47-59). When noise is detected it is then

reduced, column 11 lines 50-60. It would have been obvious to one having

ordinary skill in the art at the time the invention was made to have modified the

noise signal disclosed in Johnson with the post-process of Sluijter. Making the

post-processing means dependent of the background noise the speech quality

can be improved (see column 2 lines 55-60).

7.   Claim 33 is rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson

(US 6,415,253) in view of Adlersberg et al. (US 5,012,519) as applied to claims 1 and

28, and in further view of Bizjak et al. (US PGPub 2003/0035549) and Hermansky et al.

(US 6,098,038).

As to claim 33, Johnson and Adlersberg do not disclose specifically

sampling and adjusting means samples and adjusts a slew rate and a histogram

of said output speech signal. Bizjak teaches a signal processing method where

the slew rate is calculated and applied to non-linear smoothing which keeps the

output signal under the clipping threshold (see paragraph [0326] lines 12-17).

Hermansky teaches using an estimated noise histogram and/or a generated

noise histogram compute a spectral gain function (this is done by computing the

histogram of the noise signal's amplitudes. The peak of the smoothed histogram

is chosen as the noise amplitude estimate. These calculations are further used

to estimate the noise-to-signal ratio) (see column 4 lines 35-43). It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the spectral gain function method of Johnson with the use of histogram calculations as disclosed by Hermansky and the calculation of the slew rate as disclosed by Bizjak. Doing so would have allowed to make an accurate estimation of the noise signal and clean speech signal. Since the power of the clean speech signal is unknown, the power of the available noisy signal can be used, thus obtaining an estimate of the noisy signal-to-noise ratio (see Hermansky column 4 lines 39-41), and by the used of the slew rates it would have been easier to calculate ramping noise signals (see Bizjak paragraph [0326] lines 14-18).

Conclusion

Any inquiry concerning this communication should be directed to Josiah Hernandez whose telephone number is 571-270-1646. The examiner can normally be reached from 7:30 pm to 5:00 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Xiao Wu can be reached on (571) 272-7761. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from

the Patent Application Information Retrieval (PAIR) system. Status information

for published applications may be obtained from either Private PAIR or Public

PAIR. Status information for unpublished applications is available through

Private PAIR only. For more information about the PAIR system, see http://pair-

direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-

free).

JH

DAVID HUDSPETH
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600